



**REMOVABLE EDGE**

THICKNESS	1-3/4" (± 1/16")			
MAXIMUM SIZE	Singles Pairs DE Pairs	45 Min 4' x 8' 8' x 8'	60 Min 4' x 8' N/A N/A	90 Min 4' x 8' N/A N/A
CORE	Fire Composite			
VERTICAL EDGES (STILES)	Fire Composite with intumescent seals and matching fixed vinyl edge			
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Fire composite material; surface applied intumescent on the top rail only - sealed top & bottom rails			
FACES	Inpro Rigid Vinyl			
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, pre-consumer recycled material			
STANDARD BEVEL	1/8" in 2" or 3°			
FINISH	Woodgrains, solid colors, & elements			
ADHESIVE	Type 1 adhesive			
FACTORY MACHINING	All cutouts for mortise hardware should be made at the factory from hardware manufacturer's templates & approved shop drawings			
QUALITY STANDARDS	WDMA I.S. 1-A & AWS Section 9 Quality Standards (Bonded Core)			
WDMA PERFORMANCE LEVEL	Heavy duty; For extra heavy duty, blocking is required			
SUSTAINABILITY	<ul style="list-style-type: none"> <li>• CARB Phase 2 / TSCA VI Compliant</li> <li>• GREENGUARD GOLD or SCS Advantage Gold</li> <li>• FSC upon request, Consult VT for LEED documentation</li> <li>• Environmental Product Declaration (EPD)</li> <li>• Health Product Declaration (HPD)</li> </ul>			
DOOR WEIGHT	Approx. 8.5 lbs. / sq. ft.			
WARRANTY	Limited Lifetime. Interior use only. <a href="#">View warranty</a>			



Palladium FD-5, Removable Edge

**ADDITIONAL DOOR FEATURES & STANDARDS**

**CUTOUTS:** 5" minimum distance from door edge & the minimum distance between lite & lock cut out is 3-1/2"

**CLEARANCES:** 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7.1. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.1

**SECURITY RATING:** Class 40, ASTM 476 (highest rating possible)

**LABELING:** Positive pressure, Category A 20-minute Intertek/Warnock Hersey fire labels shall be available within size & usage approvals. Fire-rated doors must use approved lite frames. UL 10C

**PACKAGING:** Doors shall be individually poly-bagged for protection & marked as per tag openings on shop drawings

**ACCESSORIES:** Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.