



All dimensions shown are nominal before sanding, trimming and prefitting within industry standards. Specifications may be changed at manufacturer's option. Prefit and stock sizes available

#Contain no added urea-formaldehyde (NAUF)
*No added urea-formaldehyde must be specified

Blocking may affect STC rating.

Important: This door requires a standard 1-15/16" rabbetted door frame.

LEED Version 3 Credit Assistance	
Recycled Material MR 4: 1-2 points	X
Regional Material MR 5: 1-2 points	X

Credit assistance available for multiple LEED rating systems

WDMA PREMIUM GRADE EXTRA HEAVY DUTY DOOR

DOOR FEATURES:

- Finish Type:** WDMA TR-6, Catalyzed Polyurethane Factory Finish
- Veneer Match:** Book match standard. Slip or random available if specified.
- Veneer Face Assembly:** Running match standard. Center or balanced available if specified.
- Pairs and Sets:** Pair match, set match available. This application affects STC rating.
- Doors/Transoms:** Continuous match standard. End or no match available if specified.
- Vertical Edges:** Matching hardwood finished at factory (-2) with edge-before-face construction. Optional edges are: unfinished (-1) and stiles primed at factory (-9).
- Cutouts:** 3-5/16" minimum distance between lite and lock cutout and 5" minimum distance from door edge.
- Standard Bevel:** 1/8" in 2"
- Clearances:** 1/8" top, 1/8" lock and hinge stiles. See NFPA-80 6.3.1.7, 2007 edition, for bottom clearances.



DOOR STANDARDS:

- ANSI/WDMA I.S. 1-A and AWS Section 9 Quality Standards (Bonded Core). UBC 7-2-1997, Parts I and II. IBC 2000. UL 10-C.
- Top and bottom rails of door shall be factory sealed.
- Doors shall be clad in WDMA premium "A" grade wood veneer with minimum thickness 1/42" before sanding, with Type 1 adhesive containing no added urea-formaldehyde. Both domestic and exotic hardwood species available for transparent finish. Mill option face material for opaque finish.
- Sound ratings were achieved through testing at Riverbank Acoustical Laboratories in accordance with ASTM E90-90.
- Positive pressure 20-minute Intertek/Warnock Hersey fire labels shall be available within size and usage limitations. Fire-rated doors must use approved fire lite frames. Louvers are prohibited in 20-minute fire doors. Positive pressure must be noted at time of bid
- Cutouts for vision panels shall be made at the factory and shall be of sizes and locations as indicated on the drawings. Special VT acoustical lite kits, including a wood T-frame and two sheets of 5/8" laminated glass, are furnished with all non-rated doors. Maximum size is 216 square inches, or 6" wide x 36" high. Lite cut outs allowed on non-rated STC doors only.
- Hardware preparation: All cutouts for mortise hardware shall be made at the factory from hardware manufacturer's templates and approved shop drawings.
- Doors shall be individually poly-bagged for protection in transit and storage periods, and shall be marked as per tag openings on shop drawings.
- Doors will be shipped complete with VT's gasket and drop seal system