







- Doors meet AWS Section 9 Premium quality standards
- Panels are glass
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- FSC certified, subject to availability; Chain of Custody Code SW-COC-001518
- Limited 5-year warranty for interior use

FACTORY FINISH

- Doors are available with AWS System 2 pre-catalyzed lacquer factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

STICKING OPTIONS

- Reference Artistry Collection Sticking
- Custom sticking available

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
12' maximum	5'-6" maximum	3-3/8" maximum	12" maximum	12" maximum
2' minimum	1' minimum	1" minimum	5" minimum	3" minimum
Bottom Rail Width	Rail Length	Panel Height	Panel Width	Bar/Muntin Width
18" maximum	5' maximum	11'-6" maximum	5' maximum	15/16" maximum
3" minimum	6" minimum	6" minimum	6" minimum	1/2" minimum

Bar/Muntin Thickness

1-3/4" maximum

1-3/8" minimum