



- Doors meet WDMA I.S. 6-A Custom Grade quality standards
- Panels are MDF with 1/42" veneer on each side
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- Limited 5-year warranty for interior use

FACTORY FINISH

- Doors are available with WDMA TR-6 catalyzed polyurethane factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5").
- All VT factory-finished doors have sealed top and bottom rails.

STICKING OPTIONS

- Reference *Heritage Sticking Options – 5000 Series*
- Custom sticking available

DIMENSIONS (Maximum and Minimum)

| Door Height | Door Width | Door Thickness | Stile Width | Mullion Width |
|---------------------------------|--------------------------------|----------------------------------|-----------------------------|-----------------------------|
| 10'-0" maximum 1'-2" minimum | 4'-0" maximum 1'-0" minimum | 1-3/4" maximum 1-3/8" minimum | 10" maximum 3" minimum | 10" maximum 3" minimum |
| Top Rail Width | Cross/Lock Rail Width | Bottom Rail Width | Panel Height | Panel Width |
| 10" maximum 3" minimum | 10" maximum 3" minimum | 10" maximum 3" minimum | 9'-6" maximum 6" minimum | 3'-6" maximum 6" minimum |
| Bar / Muntin Width | Flat Panel Thickness | | | |
| 15/16" maximum 1/2" minimum | 5/8" maximum 5/8" minimum | | | |