



Product Update

JUN 03, 1998

#P111F

Revision 02

Applies to Flush doors

45- & 60-MINUTE DUTCH DOORS

VT is proud to announce it is now able to manufacture 45-minute and 60-minute Dutch doors. These doors can be fabricated with or without a shelf.

Using VT's approved construction, there is no need for an unsightly astragal. And, these Dutch door shelves will have the same aesthetically pleasing appearance as VT's nonrated and 20-minute Dutch shelves -- with no unsightly seams on the top of the shelf.

Machining requirements state:

1. Listed hardware must be used.
 2. All hardware and hardware configurations must meet NFPA 80 requirements.
 3. Labels are required on the top and bottom leaves.
 4. Meeting rails for top and bottom leaves require Firestop™ blocking.
 5. An intumescent strip must be mortised into the bottom rail of the top leaf.
 6. Firestop™ blocking must be used at any location where a mounting screw would otherwise enter the mineral core.
 7. Both leaves automatically latch into the door frame using cylindrical latchsets or the top leaf latching into the bottom leaf, with the bottom leaf latching into the door frame using cylindrical latchsets.
 8. May have Dutch shelves on either or both sides of the door.
- Maximum door size is 4-0 x 8-0, single opening only.

Please contact your customer service representative for pricing and availability.