



- Panels are mitered, rim banded with 1/42" veneer on each side.
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge.
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates.
- FSC certified, subject to availability; Chain of Custody Code SW-COC-0001518
- Limited 5-year warranty for interior use.

**FACTORY FINISH**

- Doors are available with AWS System 2 - pre-catalyzed lacquer factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

**STICKING OPTIONS**

- Reference *Artistry Sticking Options*
- Custom sticking available

**DIMENSIONS (Maximum and Minimum)**

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
12' maximum 2' minimum	5'-6" maximum 1' minimum	3-3/8" maximum 1" minimum	12" maximum 5" minimum	12" maximum 3" minimum
Bottom Rail Width	Rail Length	Panel Height	Panel Width	Raised Panel Thickness
18" maximum 3" minimum	5' maximum 6" minimum	11'-6" maximum 6" minimum	5' maximum 6" minimum	2-7/8" maximum 3/4" minimum