



- Doors meet AWS Section 9 Premium quality standards
- Panels are MDF with 1/42" veneer on each side
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- FSC certified, subject to availability; Chain of Custody Code SW-COC-001518
- Limited 5-year warranty for interior use

FACTORY FINISH

- Doors are available with AWS System 2 - pre-catalyzed lacquer factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

STICKING OPTIONS

- Reference *Artistry Sticking Options* for availability up to 3/4"
- Dadoed construction available for flat panels up to 1-1/4", with or without sticking
- Custom sticking available

DIMENSIONS (Maximum and Minimum)

| Door Height | Door Width | Door Thickness | Stile Width | Mullion Width |
|---------------------------|----------------------------------|------------------------------|---------------------------|------------------------------|
| 12' maximum 2' minimum | 5'-6" maximum 1' minimum | 3-3/8" maximum 1" minimum | 12" maximum 5" minimum | 12" maximum 3" minimum |
| Top Rail Width | Cross/Lock Width | Bottom Rail Width | Rail Length | Panel Height |
| 12" maximum 3" minimum | 12" maximum 3" minimum | 18" maximum 3" minimum | 5' maximum 6" minimum | 11'-6" maximum 6" minimum |
| Panel Width | Flat Panel Thickness | | | |
| 5' maximum 6" minimum | 1-1/4" standard* 1/4" minimum | | | |

*Maximum – 1/2" less than maximum door thickness.