



- Doors meet AWS Section 9 Premium quality standards
- Panels are MDF with 1/42" veneer on each side
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- FSC certified, subject to availability; Chain of Custody Code SW-COC-001518
- Limited 5-year warranty for interior use

**FACTORY FINISH**

- Doors are available with AWS System 2 - pre-catalyzed lacquer factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

**STICKING OPTIONS**

- Reference *Artistry Sticking Options* for availability up to 3/4"
- Dadoed construction available for flat panels up to 1-1/4", with or without sticking
- Custom sticking available

**DIMENSIONS (Maximum and Minimum)**

| Door Height                      | Door Width                  | Door Thickness               | Stile Width                  | Top Rail Width            |
|----------------------------------|-----------------------------|------------------------------|------------------------------|---------------------------|
| 12' maximum<br>2' minimum        | 5'-6" maximum<br>1' minimum | 3-3/8" maximum<br>1" minimum | 12" maximum<br>5" minimum    | 12" maximum<br>3" minimum |
| Cross/Lock Width                 | Bottom Rail Width           | Rail Length                  | Panel Height                 | Panel Width               |
| 12" maximum<br>3" minimum        | 18" maximum<br>3" minimum   | 5' maximum<br>6" minimum     | 11'-6" maximum<br>6" minimum | 5' maximum<br>6" minimum  |
| Flat Panel Thickness             |                             |                              |                              |                           |
| 1-1/4" standard*<br>1/4" minimum |                             |                              |                              |                           |

\*Maximum – 1/2" less than maximum door thickness.