



- Doors meet WDMA I.S. 6-A Custom Grade quality standards
- Panels are MDF with 1/42" veneer on each side
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- Limited 5-year warranty for interior use

**FACTORY FINISH**

- Doors are available with WDMA TR-6 catalyzed polyurethane factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

**STICKING OPTIONS**

- Reference *Heritage Sticking Options – 9000 Series*
- Custom sticking available

**DIMENSIONS (Maximum and Minimum)**

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
10' maximum 1'-2" minimum	4'-0" maximum 1'-0" minimum	1-3/4" maximum 1-3/8" minimum	10" maximum 3" minimum	10" maximum 3" minimum
Cross/Lock Width	Bottom Rail Width	Panel Height	Panel Width	Raised Panel Thickness
10" maximum 3" minimum	10" maximum 3" minimum	9'-6" maximum 6" maximum	3'-6" maximum 6" minimum	1'-1/8" maximum 1'-1/8" maximum

- Center vertical muntin required if pre-fit width of louver is greater than 16"