


HERITAGE COLLECTION: SCLC-3

3-PLY BONDED STRUCTURAL COMPOSITE LUMBER CORE NON-RATED, 20-, & 45-MINUTE POSITIVE PRESSURE

PRIMED HDF

THICKNESS	1.7//
THICKNESS	1-3/4", 1-3/8", 2", or 2-1/4" (±1/16")
MAXIMUM SIZE	4'-0" x 10'-0" maximum, for oversized doors please consult VT; see fire door capability chart for rated doors
CORE	Structural Composite Lumber Core (SCLC), 70% of door construction weight
VERTICAL EDGES (STILES)	Structural Composite Lumber (SCL) or Fire Composite as required with finished mill option (primed or painted edges)
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) - Sealed Top & Bottom Rails
FACES	Primed High Density Fiberboard (HDF)
STANDARD BEVEL	1/8" in 2" or 3°
FINISH	Primed; Wood accessories available finished to match
ADHESIVE	Type 1 adhesive
FACTORY MACHINING	Pre-drilled hinge pilot holes; all cutouts for mortise hardware should be made at the factory from hardware manufacturer's templates & approved shop drawings
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core)
WDMA PERFORMANCE LEVEL	Extra heavy duty
SUSTAINABILITY	 CARB Phase 2 / TSCA VI Compliant GREENGUARD GOLD or SCS Indoor Advantage Gold FSC upon request, Consult VT for LEED documentation Environmental Product Declaration (EPD) Health Product Declaration (HPD)
DOOR WEIGHT	Approx. 6 lbs./sq. ft.
WARRANTY	Limited Lifetime, Interior use only. <u>View warranty</u>



SCLC-3 (5508H, 5P08H, 808H, 8P08H)

ADDITIONAL DOOR FEATURES

CUTOUTS; 5" minimum distance from door edge & the minimum distance between lite & lock cut out is 1-1/2" non-rated & 20-minute, 5" lite to lock (45-minute)

CLEARANCES; 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.

SECURITY RATING: Class 40, ASTM 476 (highest rating possible)

 $\underline{\mathsf{LABELING:}}\ \mathsf{Positive}\ \mathsf{pressure}, \mathsf{Category}\ \mathsf{A}\ \mathsf{20}\text{-minute Intertek/Warnock}\ \mathsf{Hersey}\ \mathsf{fire}\ \mathsf{labels}\ \mathsf{per}\ \mathsf{NFPA}\ \mathsf{80}\ \mathsf{4.2}\ \mathsf{Fire}\text{-rated}\ \mathsf{doors}\ \mathsf{must}\ \mathsf{use}\ \mathsf{approved}\ \mathsf{lite}\ \mathsf{frames.}\ \mathsf{UL}\ \mathsf{10C}$

PACKAGING: Doors shall be individually poly-bagged by request for protection & marked as per tag openings on shop drawings ACCESSORIES: Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others.

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.







