

## PRIMED HDF

THICKNESS	1-3/4" (± 1/16")
MAXIMUM SIZE	Please consult VT for maximum sizes; See fire capability chart for rated doors
CORE	Agrifiber Core, ANSI A208.1, Grade LD-2, 70% of door construction weight, Composed of pre-consumer rapidly renewable material
VERTICAL EDGES (STILES)	Structural Composite Lumber (SCL) or Fire Composite as required with mill option (primed or painted) edges
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) or Fire Composite as required- sealed top & bottom rails
FACES	Primed High Density Fiberboard (HDF)
STANDARD BEVEL	1/8" in 2" or 3"
FINISH	Factory primed or opaque finish, wood accessories available finished to match
ADHESIVE	Type 1 adhesive
FACTORY MACHINING	Pre-drilled hinge pilot holes, all cutouts for mortise hardware should be made at the factory from hardware manufacturer's templates & approved shop drawings
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core)
WDMA PERFORMANCE LEVEL	Heavy duty. For extra heavy duty, blocking for hardware is required
SUSTAINABILITY	<ul style="list-style-type: none"> <li>• CARB Phase 2 / TSCA VI Compliant</li> <li>• GREENGUARD GOLD or SCS Indoor Advantage Gold</li> <li>• FSC upon request, Consult VT for LEED documentation</li> <li>• Environmental Product Declaration (EPD)</li> <li>• Health Product Declaration (HPD)</li> </ul>
DOOR WEIGHT	Approx. 5.5 lbs./sq. ft.
WARRANTY	Limited Lifetime, Interior use only. <a href="#">View warranty</a>



WSPC-3 (5509H, 5P09H, 9P09H, 909H)

### ADDITIONAL DOOR FEATURES

**PAIRS & SETS:** Pair match standard, set match available

**DOORS/TRANSOMS:** Continuous match standard, End or no match available

**CUTOUTS:** 4" minimum distance from door edge & the minimum distance between lite & lock cut out is 3-5/16"

**CLEARANCES:** 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7.1. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.1

**SECURITY RATING:** Class 40, ASTM 476 (highest rating possible)

**LABELING:** Positive pressure, Category A 20-minute Intertek/Warnock Hersey fire labels shall be available within size & usage approvals.

Fire-rated doors must use approved lite frames, UL 10C

**PACKAGING:** Doors shall be individually poly-bagged by request for protection & marked as per tag openings on shop drawings

**ACCESSORIES:** Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others.

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.