

- **TOP RAIL:#**
3-3/8" Structural Composite Lumber (SCL) FSC certified with surface-applied intumescent
- **VERTICAL STILES:#**
1-3/8" Structural Composite Lumber (SCL) FSC certified with matching hardwood edge.
Crossbands and intumescent concealed at edge
- **CORE:**
Sound Core Composite* 70% of door construction weight.
CROSSBANDS:
High Density Fiber (HDF), no added urea-formaldehyde HDF, or FSC certified*
20% of door construction weight, certified composed of pre-consumer recycled material.
- **FACES:**
"A" grade wood veneer, Mill Option Paintable Surface, FSC controlled wood, or FSC certified*, unless otherwise specified.
- **FINISHED THICKNESS:**
1-3/4" (± 1/16")
- **BOTTOM RAIL:#**
3-3/8" Structural Composite Lumber (SCL) FSC certified.

All dimensions shown are nominal before sanding, trimming and prefitting within industry standards. Specifications may be changed at manufacturer's option. Prefit and stock sizes available.

Contain no added urea-formaldehyde.
* No added urea-formaldehyde or FSC Certified must be specified.

*****No additional blocking required.
Blocking may affect STC rating.**

Important: This door requires a standard 1-15/16" rabbetted door frame.

LEED Version 3 Credit Assistance


Recycled Material MR 4: 1-2 points	X
Regional Material MR 5: 1-2 points	X
Certified Wood MR 7: SCS-COC-004128	X
Low-Emitting Material EQ 4.4	X

Credit assistance available for multiple LEED rating systems

AWS/WDMA CUSTOM GRADE EXTRA HEAVY DUTY DOOR

DOOR FEATURES:

- Finish Type:** WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane), Primed Factory Finish or Opaque Paint.
- Veneer Match:** Book match standard. Slip or random available if specified.
- Veneer Face Assembly:** Running match standard. Center or balanced available if specified.
- Pairs and Sets:** Pair match
- Vertical Edges:** (visible surface) Matching hardwood finished at factory (-2) with edge-before-face construction. Optional edges are: unfinished (-1) and stiles primed at factory (-9).
- Cutouts:** 3-5/16" minimum distance between lite and lock cutout and 5" minimum distance from door edge.
- Standard Bevel:** 1/8"
- Clearances:** 1/8" top, 1/8" lock and hinge stiles. See NFPA-80 6.3.1.7.1, 2013 Edition. Bottom clearance 3/4" max. (bottom of the door to top finish floor) See NFPA-80 4.8.4.1, 2013 edition.
- Screw Holding and Split Resistance:** Refer to Customer Service Update #CS119F (www.vtindustries.com/doors/csupdates)



*20 min Pairs available STC 39

DOOR STANDARDS:

- WDMA I.S. 1-A-2011 and AWS, Edition 2, Section 9 Quality Standards (Bonded Core).
- Top and bottom rails of door shall be factory sealed.
- Doors shall be clad in AWS/WDMA custom "A" grade wood veneer with minimum thickness 1/42" before sanding, with Type 1 adhesive containing no added urea-formaldehyde. Both domestic and exotic hardwood species available for transparent finish. Mill option face material for opaque finish. Premium "AA" grade wood veneer available by request.
- Sound ratings were achieved through testing at Intertek- Architectural Testing Inc. in accordance with ASTM E90-90.
- Positive pressure 20-minute Intertek/Warnock Hersey fire labels shall be available within size and usage limitations. Fire-rated doors must use approved fire lite frames. Louvers are prohibited in 20-minute fire doors. UL 10C
- Hardware preparation: All cutouts for mortise hardware shall be made at the factory from hardware manufacturer's templates and approved shop drawings.
- Doors shall be individually poly-bagged for protection in transit and storage periods, and shall be marked as per tag openings on shop drawings.
- Cutouts for vision panels shall be made at the factory and shall be of sizes and locations as indicated on the drawings. See STC chart for lite sizes by STC rating.
- Door bottoms, sweeps, thresholds, gasketing, lite kits and glass may be supplied by others or VT.