



- Panels are mitered, rim based with 1/42" veneer on each side
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- FSC certified Structural Composite Lumber Core available; Chain of Custody Code SW-COC-001518
- No added urea-formaldehyde, available by request
- Limited lifetime warranty for interior use

FACTORY FINISH

- Doors are available with AWS System 2 - pre-catalyzed lacquer factory finish
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")
- All VT factory-finished doors have sealed top and bottom rails

STICKING OPTIONS

- Reference Artistry Sticking Options for availability
- Custom sticking available

* Note: Louvers greater than 16" wide require center divider

DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
12' maximum 2' minimum	5' maximum 1' minimum	2-1/4" maximum 1-3/8" minimum	12" maximum 5" minimum	12" maximum 3" minimum
Cross/Lock Width	Bottom Rail Width	Rail Length	Panel Height	Panel Width
12" maximum 3" minimum	10" maximum 3" minimum	5' maximum 6" minimum	11'-6" maximum 6" minimum	5' maximum 6" minimum
Flat Panel Thickness				
1-1/4" maximum 1/4" minimum				