



- Doors meet WDMA I.S. 6-A Custom Grade quality standards
- Stiles & rails are PBC for non-rated & 20-minute with 1/42" veneer on panels & 1/16" veneer on stiles & rails
- Factory machined to exact requirements for hardware
- FSC certified by request, subject to availability; Chain of Custody Code PWC-COC-000408
- No added urea-formaldehyde, available by request
- Life of original installation

FACTORY FINISH

- Doors are available with WDMA TR-6 water reducible, urethane based, acrylic lacquer factory finish
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")

STICKING OPTIONS

- Standard & custom sticking available

DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
10'-0" maximum 1'-2" minimum	4'-0" maximum 1'-0" minimum	2-1/4" maximum 1-3/8" minimum	10" maximum 3" minimum	10" maximum 3" minimum
Bottom Rail Width	Rail Length	Panel Height	Panel Width	
10" maximum 3" minimum	9'-6" maximum 6" minimum	3'-6" maximum 6" minimum	15/16" maximum 1/2" minimum	

*20,45,60,90-minute fire ratings available depending upon rail size specified