



- Doors meet WDMA I.S. 6-A Custom Grade quality standards
- Stiles & rails are PBC for non-rated & 20-minute with 1/42" veneer on panels & 1/16" veneer on stiles & rails
- Factory machined to exact requirements for hardware
- FSC certified by request, subject to availability; Chain of Custody Code PWC-COC-000408
- No added urea-formaldehyde, available by request
- Life of original installation

FACTORY FINISH

- Doors are available with WDMA TR-6 water reducible, urethane based, acrylic lacquer factory finish
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")

STICKING OPTIONS

- Standard & custom sticking available

DIMENSIONS (Maximum and Minimum)

| Door Height | Door Width | Door Thickness | Stile Width | Top Rail Width |
|---------------------------------|--------------------------------|----------------------------------|--------------------------------|---------------------------|
| 10'-0" maximum 1'-2" minimum | 4'-0" maximum 1'-0" minimum | 2-1/4" maximum 1-3/8" minimum | 10" maximum 3" minimum | 10" maximum 3" minimum |
| Bottom Rail Width | Rail Length | Panel Height | Panel Width | |
| 10" maximum 3" minimum | 9'-6" maximum 6" minimum | 3'-6" maximum 6" minimum | 15/16" maximum 1/2" minimum | |