



- Doors meet AWS Section 9 Premium quality standards
- Panels are glass
- Stiles & rails are PBC for non-rated & 20-minute with 1/42" veneer on panels & 1/16" veneer on stiles & rails
- Factory machined to exact requirements for hardware
- FSC certified by request, subject to availability; Chain of Custody Code PWC-COC-000408
- No added urea-formaldehyde, available by request
- Life of original installation

FACTORY FINISH

- Doors are available with WDMA TR-6 water reducible, urethane based, acrylic lacquer factory finish
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")
- All VT factory-finished doors have sealed top and bottom rails

STICKING OPTIONS

- Standard & custom sticking available

DIMENSIONS (Maximum and Minimum)

| Door Height | Door Width | Door Thickness | Stile Width | Top Rail Width |
|--------------------------------|---------------------------|----------------------------------|-----------------------------|------------------------------|
| 10' maximum 1-2" minimum | 4' maximum 1' minimum | 1-3/4" maximum 1-3/8" minimum | 10" maximum 3" minimum | 10" maximum 3" minimum |
| Bottom Rail Width | Rail Length | Panel Height | Panel Width | Bar/Muntin Width |
| 10" maximum 3" minimum | 10" maximum 3" minimum | 9'-6" maximum 6" minimum | 3'-6" maximum 6" minimum | 5/8" maximum 5/8" minimum |
| Bar/Muntin Thick- | | | | |
| 15/16" maximum 1/2" minimum | | | | |