



- Doors meet AWS Section 9 Premium quality standards
- Panels are glass
- Stiles & rails are PBC for non-rated & 20-minute with 1/42" veneer on panels & 1/16" veneer on stiles & rails
- Factory machined to exact requirements for hardware
- FSC certified by request, subject to availability; Chain of Custody Code PWC-COC-000408
- No added urea-formaldehyde, available by request
- Life of original installation

### FACTORY FINISH

- Doors are available with WDMA TR-6 water reducible, urethane based, acrylic lacquer factory finish
- VT color choices are available or custom color matching by submitting a physical sample ( minimum 3" x 5" )
- All VT factory-finished doors have sealed top and bottom rails

### STICKING OPTIONS

- Standard & custom sticking available

### DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
10' maximum 1-2" minimum	4' maximum 1' minimum	1-3/4" maximum 1-3/8" minimum	10" maximum 3" minimum	10" maximum 3" minimum
Bottom Rail Width	Rail Length	Panel Height	Panel Width	Bar/Muntin Width
10" maximum 3" minimum	10" maximum 3" minimum	9'-6" maximum 6" minimum	3'-6" maximum 6" minimum	5/8" maximum 5/8" minimum
Bar/Muntin Thick-				
15/16" maximum 1/2" minimum				