



- Doors meet AWS Section 9 Premium quality standards
- Stiles & rails are PBC for non-rated & 20-minute with 1/42" veneer on panels & 1/16" veneer on stiles & rails
- Factory machined to exact requirements for hardware
- FSC certified by request, subject to availability; Chain of Custody Code PWC-COC-000408
- No added urea-formaldehyde, available by request
- Life of original installation

FACTORY FINISH

- Doors are available with WDMA TR-6 water reducible, urethane based, acrylic lacquer factory finish
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")
- All VT factory-finished doors have sealed top and bottom rails

STICKING OPTIONS

- Standard & custom sticking available

DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
10' maximum 1-2' minimum	4' maximum 1' minimum	1-3/4" maximum 1-3/8" minimum	10" maximum 3" minimum	10" maximum 3" minimum
Cross/Lock Width	Bottom Rail Width	Panel Height	Panel Width	Flat Panel Thickness
10" maximum 3" minimum	10" maximum 3" minimum	9'-6" maximum 6" minimum	3'-6" maximum 6" minimum	1-1/8" maximum 1-1/8" minimum

* Center vertical muntin required if pre-fit width of louver is greater than 16"