



STILE & RAIL DOOR ELEVATIONS -1052

JOB NUMBER: _____ PAGE: _____ / _____

JOB NAME: _____

STANDARDS:*

Top Rail: 6"
Bottom Rail: 10"

Stile: 6"
Mullion: 3-5/8"

* Standard component dimensions may vary on fire rated doors. Refer to the Stile & Rail Brochure.

Heritage

SS1052

SA1052

SC1052

Heritage Only Heritage Only

Dimensions

- Standard – see above
- Custom – fill in below

Top Rail: _____ Bottom Rail: _____

Hinge and Lock Stiles: _____ Mid Rail: _____

Panel Dimensions are Equal: _____

Sticking

Heritage Collection

- Ovolo
- Square
- Ogee
- Mission
- Classic
- Other- Supply Drawing

Panels[#]

- Raised Step
- Flat

[†]Panel veneer grain will run vertical unless otherwise noted

Glass (Advise which panels are glass)**

Supplied By:	Thickness/Type
<input type="checkbox"/> VT <input type="checkbox"/> Other <input type="checkbox"/> N/A	<input type="checkbox"/> 1/4" Tempered*** <input type="checkbox"/> 3/16" Clear Firelight® <input type="checkbox"/> 1/4" Wire <input type="checkbox"/> Other: _____

**Glass opening dimensions will vary depending on prefit door size

***If diagonal dimension of tempered glass is less than 13", glass will be substituted with laminated safety glass

[#]Panel dimensions will vary depending on prefit door size
Dimensions are to cutout (do not include sticking height). Panel and glass dimensions will vary depending on prefit door size

