



Flush Door P.O. Attachment

VT #: _____ PO #: _____ Date: _____

Distributor: _____ Contact: _____

Project Name: _____ Contact: _____

Ship To Address: _____

Job Phone: _____ Job Fax: _____

Quantity of Leaves: _____ Ship Date Requested: _____

Specifications

Fire Rating: Neutral Pressure Positive Pressure Frame: Hollow Metal Aluminum

Wood Frames by VT (Per attached Frame Elevations)

Quality Standards: WDMA I.S.1A-11 or AWS 2009* or AWI QCP or Custom A or Premium AA

Collection Heritage

Environmental: No Added UF FSC Controlled FSC

Veneer: Species, cut, match, Assembly: _____
 "A" "AA"

HPDL: Manufacturer, color #, and finish #: _____
 VGS- vertical grade HGS- horizontal grade

Stile Finish: -1 unfinished -2 finished -3 HPDL -4 painted -9 primed
(Rails sealed unless otherwise noted below).

Extra Blocking: Wide Stiles _____ Wide Rails _____

Lock Blocks: *(specify quantity per door)* _____
Blocking on mineral core doors only unless noted. Lock block size is determined by hardware requirements.

Rated Lite Stops Cutout only 110 Veneer Wrapped Vision Panel
 VT1F (Heritage Only) 110 Metal Vision Panel

Non-rated & 20-minute lite stops: 110 Metal Vision Panel 110 Veneer Wrapped Vision Panel Cut- out only
Heritage Only: VT1 VT3 VT7 VT9
 VT15 Visible Cutout

Lite size provided are:

Louvers: Supplied by Others Supplied by VT- Specify Type: _____

Glass: Supplied By: Others VT
Type/Thickness: 1/4" Tempered 1/4" Wirelite NT 3/16" Keralite FRF Other- Specify: _____

Factory Finish: VT Color Choice Sample Name: _____ Date on Sample: _____
Approved Custom Color Match #: _____
(Approved VT Sample must be provided on all custom color matches.)

Undercut: Rated: _____ Non-Rated: _____

Bevel: 1/8" in 2" Other: _____

Exit Devices Location: Per Template Other: _____

Hardware Locations per: _____
Intertek/Warnock Hersey fire labels will be used.

Notes: _____

PLEASE RETURN THIS FORM COMPLETED WITH PURCHASE ORDER.

*AWS 2009 Industry Standard includes most recent Errata.