

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/16/2010 Revision date: 06/19/2015 Supersedes: 02/16/2010 Version: 2.0

1/8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Trade name : LG HI-MACS® Sheets (Acrylic Solid Surface Material)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified use : Surface Material

#### 1.3. Details of the supplier of the safety data sheet

LG Hausys America, Inc. 900 Circle 75 Parkway Suite 1500 Atlanta, GA 30339

Tel: 678-486-8250

#### 1 4 **Emergency telephone number**

Emergency number : 706-879-3200 (Product/Safety)

800-255-3924 (Chemtel- Transport Emergency)

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification<sup>†</sup>

Comb. Dust H232 Skin Sens. 1 H317

Full text of H-statements: see section 16

#### 2.2. Label elements

### Labelling

This product meet the criteria of atrticle definition and therefore is exempt from labeling.

#### 2.3. Other hazards

Hazards not thoerwise identified

: "LG Hi-Macs" Solid Surface Material is not hazardous and does ot pose physical hazards and /or health risk as supplied or shipped. However, operations such as sawing, routing, drilling and sanding can generate dust. High concentrations of dust can cause reversible physical irritation to eyes, nose and respiratory passages and cause coughing and sneezing. Even though there are no exposure limits established for dust from Hi-Macs®, avoid breathing dust.

"LG Hi-Macs" Solid Surface Material does not release any gas or vapors at ambient conditions. At higher temperatures (>3000C / 5720F), small amounts of methyl methacrylate (MMA) could be released, amount dependent upon temperature, time and other variables. Vapors at high concentration can cause skin and respiratory irritation. Overexposure to vapors can cause headache, nausea, weakness and lung irritation with cough, discomfort and shortness of breath. Individuals with pre-existing diseases of the lungs or skin may have increased susceptibility to the effects of overexposure to methyl methacrylate.

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

### **SECTION 3: Composition/information on ingredients**

Not applicable

This product meets the criteria of article definition and does not pose any physical hazards and health risk as supplied.

06/22/2015 EN (English)

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Name	Product identifier	%
Aluminium hydroxide (component)	(CAS No) 21645-51-2	52 - 62
Methyl methacrylate polymer (component)	(CAS No) 9011-14-7	30 - 50
Methyl methacrylate (component)	(CAS No) 80-62-6	<= 1
Copolymer colorants (component)	(CAS No) Not available	1 - 5

#### 3.2. Mixture

Not applicable

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Inhalation is unlikely a route of exposure at ambient temperature.

In case of inhalation of dust or vapor from processing: Allow breathing of fresh air. Allow the

victim to rest. Consult a physician if breathing is difficult or if symptoms persist.

First-aid measures after skin contact : Unlikely a route of exposure as supplied. In case of generation of dust or vapor from

processing: Wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

First-aid measures after eye contact : Unlikely a route of exposure as supplied. Rinse immediately with plenty of water. Obtain

medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Unlikely a route of exposure as supplied. Rinse mouth. Obtain emergency medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Not a flammable solid, bur cabn burn. Use extinguishing media appropriate for surrounding fire.

Foam. Dry powder. Carbon dioxide. Water spray.

Unsuitable extinguishing media : None kown

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable but burns.

Explosion hazard : Avoid generation of dust; fine dust dispersed in air in sufficient concentration, and in the

presence of an ignition source is a potential dust explosion hazards.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire.

Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

06/22/2015 EN (English) 2/8

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: In case of generation of dust from processing: Spills of this product as dust, present a serious slipping hazard.

Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

### 6.1.2. For emergency responders

Protective equipment

: Equip cleanup crew with proper protection. Use appropriate PERSONAL PROTECTIVE EQUIPMENT and recover undamaged and minimally contaminated material for reuse and reclamation.

Emergency procedures

: In case of generation of dust from processing: Ventilate area.

#### 6.2. Environmental precautions

contain according to the local, state, National regulation.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: In case of generation of dust or vapor from processing: Review HANDLING Section before proceeding with clean up. Use appropriate tools to put spilled solids in a convenient waste disposal container. Review FIRE FIGHTING MEASURES and HANDLING Sections before proceeding with clean up.

Avoid contact with skin and eyes. Avoid breathing dust and vapurs. On land, sweep or shovel into suitable containers. Minimize generation of dust. Avoid raising airborne dust. Avoid dispersal of dust in the air (i.e., cleaning dust surfaces with compressed air). Non-sparking tools should be used.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed Precautions for safe handling

- : In case of generation of dust from processing: This product presents a serious slipping hazard.
- : Loading/ Unloading: Sheets should be unloaded with a forklift or other lifting device capable of handling pallets safely. If a lifting device is not available, always carry a single sheet in the vertical position and wear proper safety shoes and protective gloves as sheets may have sharp edges. Carrying should be done by two people facing each other on short sides with one hand under the bottom edge for support and the other hand on the top edge to control the sheet.

Processing/ Machining: Avoid breathing dust. Avoid breathing fumes generated during heating. Temperatures reached while thermoforming could be high enough to release some methyl methacrylate. Machining operations during fabrication, such as sawing, sanding or routing, create friction and may result in temperatures high enough to release small amounts of methyl methacrylate at the cutting tool surface. Ensure good ventilation of the work station. Wear personal protective equipment. Avoid raising airborne dust. Avoid contact with skin and eyes. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build statics electricity charges when subjected to the friction of transfer and mixture operations. Provide adequate precautions, such as electrical grounding and bonding or inert atmospheres.

Hygiene measures

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: No specific storage is required. Be sure that it is not necessary to strain to reach materials and that shelves are not overloaded.

Incompatible materials : No additional information available.

### 7.3. Specific end use(s)

No additional information available

06/22/2015 EN (English) 3/8

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters<sup>‡</sup>

Methyl methacrylate (80-62-6)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	410 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Aluminium hydroxide (21645-51-2)		
OSHA	OSHA PEL (TWA) (mg/m³) Aluminum	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
ACGIH	ACGIH TWA (mg/m³) Aluminum	1 mg/m³ (respirable fraction)

### 8.2. Exposure controls

Appropriate engineering controls

: Use adequate ventilation to keep employee exposures to airborne concentrations below recommended limits for dust or vapors from operations such as machining, cutting, routing, sanding, etc. In addition, provide for appropriate exhaust ventilation and dust collection at machinery.

In case of generation of dust or vapour from processing: It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust dusts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area. Use only appropriately classifies electrical equipment and powered industrial trucks.

Personal protective equipment

: Safety glasses. Gloves. Protective clothing. Respiratory protection.



Skin and body protection

Wear leather or cotton gloves when handling pieces to protect against cuts and abrasions. Safety shoes are also recommended whenever handling large pieces of material. Hearing protection may also be required during machining operations, depending on noise (decibel) levels.

Eye protection

: Wear safety glasses during operations such as sawing, sanding, drilling, or routing. Also, machining operations could require safety goggles and face-shield to protect against flying debris/particles.

Respiratory protection

: In case of insufficient or inadequate ventilation during machining operations or if airborne particulate concentrations or vapors are expected to exceed permissible exposure limits, use a NIOSH approved air-purifying respirator. Respirators should be selected based on the form and concentration of the air contaminant and in accordance with OSHA Respiratory Protection Standard(s).

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: SolidAppearance: SheetColor: Varies

Odor : None-Odorless
Odor threshold : Not applicable
pH : No applicable
Relative evaporation rate (butyl acetate=1) : No data available

06/22/2015 EN (English) 4/8

<sup>&</sup>lt;sup>‡</sup> The work place exposure limits are not applicable to products as is supplied. The provided work place limits shall considered during processing resulting to generation of dust and/or vapors.

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Melting point : No data available : No data available Freezing point Boiling point : Not applicable Flash point : Not applicable Auto-ignition temperature : Not applicable Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure Not applicable Relative vapour density at 20 °C : No data available Relative density : 1.7 - 1.8 (Water=1) Solubility Not soluble in water Log Pow : No data available Log Kow No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties No data available Oxidising properties : No data available Explosive limits : No data available

### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable at normal temperatures and storage conditions.

### 10.3. Possibility of hazardous reactions

Polymerization will not occur in solid state.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

None reasonably foreseeable, non-corrosive.

### 10.6. Hazardous decomposition products

Frictional heat from machining that could reach or exceed a temperature of 300°C (572°F) could result in the release of a small amount of methyl methacrylate vapor.

Thermal Decomposition products: carbon monoxide, methyl methacrylate, and smoke.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Methyl methacrylate (80-62-6)	
LD50 oral rat	7900 mg/kg
LC50 inhalation rat (ppm)	4632 ppm/4h
ATE US (oral)	7900.000 mg/kg bodyweight
ATE US (gases)	4632.000 ppmv/4h

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

06/22/2015 EN (English) 5/8

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Methyl methacrylate (80-62-6)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

Methyl methacrylate (80-62-6)	
LC50 fish 1	243 - 275 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	69 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	125.5 - 190.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

#### 12.2. Persistence and degradability

Not established.

#### 12.3. Bioaccumulative potential

Not established.

Methyl methacrylate (80-62-6)	
Log Pow	0.7

#### Mobility in soil 12.4.

No additional information available

#### 12.5. Other adverse effects

Effect on ozone layer : No additional information available Effect on the global warming : No additional information available

### **SECTION 13: Disposal considerations**

#### Waste treatment methods 13.1.

: Preferred waste disposal options include recycling, landfill, or incineration, when in compliance Waste disposal recommendations

with applicable Federal, State/Provincial, and Local regulations.

### **SECTION 14: Transport information**

In accordance with DOT

Not regulated for transport

## **Additional information**

Other information : No supplementary information available.

### **ADR**

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

06/22/2015 6/8 EN (English)

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methyl methacrylate CAS No 80	-62-6 <= 1
-------------------------------	------------

Methyl methacrylate (80-62-6)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %

### 15.2. International regulations

### **CANADA**

No additional information available

Methyl methacrylate polymer (9011-14-7)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification Uncontrolled product according to WHMIS classification criteria		
Methyl methacrylate (80-62-6)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification  Class B Division 2 - Flammable Liquid  Class D Division 2 Subdivision B - Toxic material causing other toxic effects		

### **EU-Regulations**

No additional information available

Methyl methacrylate (80-62-6)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

### 15.2.2. National regulations

### Methyl methacrylate polymer (9011-14-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### Methyl methacrylate (80-62-6)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

Listed on Turkish inventory of chemical

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

06/22/2015 EN (English) 7/8

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### **SECTION 16: Other information**

Abbreviations and acronyms

: ACGIH (American Conference of Government Industrial Hygienists). ATE - acute toxicity estimate. CAS (Chemical Abstracts Service) number. CLP - Classification, Labelling and Packaging. HCS - Hazard Communication Standard. IARC (International Agency for Research on Cancer). OSHA - Occupational Safety and Health Administration. Overland transport (ADR). STEL- Short-Term Exposure Limit. TLV- Threshold Limit Value. TWA- Time Weighted Average. TSCA - Toxic Substance Control. European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. European Agreement concerning the International Carriage of Dangerous Goods by Road. Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. International Agency for Research on Cancer. Median effective concentration. International Air Transport Association. Median lethal concentration. Median lethal dose.

Other information

Refer to NFPA 654, Standard for the Prevention of Fire and Dust explosions from the Manufctureing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

#### Full text of H-statements:

 Comb. Dust	Combustible dust
 Skin Sens. 1	Sensitisation — Skin, category 1
 H232	May form combustible dust concentrations in air
 H317	May cause an allergic skin reaction

The information on this sheet is not a specification and does not guarantee specific properties. The information is intended to provide general knowledge as to health and safety based upon our knowledge of the handling, storage and use of the product. It is not applicable to unusual or non-standard uses of the product or where instruction or recommendations are not followed.

06/22/2015 EN (English) 8/8