

ELECTRIC & OPEN BACK STRIKES

CORE TYPE	NON-RATED	AVAILABLE		CORE RESTRICTIONS	ELECTRIC STRIKE RESTRICTIONS
		ELECTRIC	OPEN BACK		
Non-Rated	Non-Rated	Yes	Yes		

CORE TYPE	20-MINUTE	AVAILABLE		CORE RESTRICTIONS	ELECTRIC STRIKE RESTRICTIONS
		ELECTRIC	OPEN BACK		
Structural Composite Lumber	20-Minute	Yes	No		The electric strikes must be listed and approved by UL
Particleboard	20-Minute	Yes	No		
Agrifiber	20-Minute	Yes	No	5" wide Pyroforce stile or 5" blocking is required	Listed electric strikes to manufacturers' installation instructions may be used
Pyroforce	20-Minute	Yes	No		
Lead-Lined	20-Minute	No	No	Unavailable	Unavailable

CORE TYPE	45-MINUTE	AVAILABLE		CORE RESTRICTIONS	ELECTRIC STRIKE RESTRICTIONS
		ELECTRIC	OPEN BACK		
Particleboard	45-Minute	No	No	Unavailable	Unavailable
Agrifiber	45-Minute	Yes	No	5" wide Pyroforce stile or 5" blocking is required	Listed electric strikes to manufacturers' installation instructions may be used
Pyroforce	45-Minute	No	No	5" Wide Pyroforce stile Maximum Size: 8'-0" wide by 8'-0" tall	
Lead-Lined	45-Minute	No	No	Unavailable	Unavailable

CORE TYPE	60-90-MINUTE	AVAILABLE		CORE RESTRICTIONS	ELECTRIC STRIKE RESTRICTIONS
		ELECTRIC	OPEN BACK		
All Core Types	60-90-Minute	No	No	Unavailable	Unavailable