



**Architectural
Wood Doors**

HERITAGE / PALLADIUM COLLECTION:STC

ACOUSTIC CORE DOORS
NON-RATED, 20-MINUTE POSITIVE PRESSURE
SG14 (STC 46-52) MULTI-PLY CONSTRUCTION

WOOD VENEER, HPDL, INPRO RIGID VINYL, MDO, PAINT GRADE VENEER

THICKNESS	1-3/4" (± 1/16")
SIZE	Min. 2'-0" x 6'-0", Max. 4'-0" x 8'-0"
CORE	SG14 Acoustic Core, 70% of door construction weight
LEAD	Contains an 1/8" overall lead thickness
VERTICAL EDGES (STILES)	Structural Composite Lumber (SCL) with matching/compatible wood veneer, matching HPDL, matching fixed vinyl, or finish mill option (primed or painted) edges
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) - Sealed Top & Bottom Rails
FACES	Wood Veneer (A Grade Book & Running standard), HPDL, Inpro® Rigid Vinyl (.040"), MDO, Paint Grade Veneer, some limitations may apply
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, Pre-consumer recycled material
STANDARDS	Bevel: 1/8" in 2" or 3" Fire rated clearance per NFPA 80, Fire rating per UL 10C/NFPA252 Type 1 Polyvinyl Acetate (PVA) Adhesive
FINISH	Transparent; WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) Primed; Wood accessories available primed; Additional field sanding and cleaning required prior to application of paint Opaque; WDMA OP-8/AWS System 9 Laminate; Woodgrains, Solid Colors, and Patterns Palladium; Woodgrains, Solid Colors, and Elements
HARDWARE/LITES	Butt Hinges, Electric Hinges, Cylindrical Locks, Mortise Locks, Rim and Surface Exit Devices, limitations may apply Pre-drilled hinge pilot holes Refer to Lite/Lock Cutout Margins Technical Bulletin Refer to VT Soundsource for lite approvals
ACOUSTICAL RATING	STC 46, 47, 48, 49, 50, 51, 52; ASTM 90 / ASTM E413 Tested in 18-gauge, welded fully grouted steel frame Latching required to maintain STC rating Test Reports available
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core) Custom Grade (standard) or Premium Grade (available)
WDMA PERFORMANCE LEVEL	Heavy Duty For Extra Heavy Duty, blocking for hardware is required
SUSTAINABILITY	CARB Phase 2 / TSCA VI Compliant GREENGUARD GOLD FSC® upon request, Environmental Product Declaration (EPD), Health Product Declaration (HPD) Consult VT for LEED documentation Refer to VT Sustainability page
WARRANTY	Limited Lifetime, Interior use only, reference VT Warranty

ACOUSTICAL CAPABILITIES	STC 46-49	STC 49	STC 50	STC 50-51	STC 52
FIRE RATING	N/A	N/A	N/A	NR-20M	NR-20M
PAIRED OPENINGS	N/A	N/A	N/A	N/A	N/A
LITES	Available VT Soundsource	N/A	Available VT Soundsource	N/A	N/A
GASKET SYSTEMS	VT7	VT7	VT5, VT6	VT5, VT6, VT7	VT5, VT6
WEIGHT (PER SQ FOOT)	12lbs	12lbs	12lbs	12lbs	12lbs

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



**CUSTOMER
SERVICE**

800.827.1615
info@vtindustries.com
vtindustries.com



© 2026 VT Industries, Inc. All rights reserved 09-2026