



- Doors meet WDMA/AWS Custom or Premium Grade quality standards
- Factory machined to exact requirements for hardware
- 20-, 45-, 60-, 90-minute stile and rail fire ratings
- 20-minute: true divided lite; 45-90-minute: taped on grillwork over single sheet of glass
- FSC® certified upon request (non-rated & 20-minute); NC-COC-000729
- No added urea-formaldehyde (NAUF) available upon request
- Matching wood jambs available
- Sketch-face veneers, laser marquetry, inlay & split species designs available
- Limited lifetime warranty for interior use

FACTORY FINISH

- WDMA TR-8/ System 10 Water-based UV cured acrylated polyurethane is standard. Primed and opaque coatings also available.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")

Note: Some species are only available unfinished. Please contact your sales representative with questions.

GLASS OPTIONS

- Stile and Rail doors are available with a variety of glass types and thicknesses; the amount of glass allowable per door is contingent upon the door size, fire-rating, and other special attributes of the door. Please contact your sales representative for more information.

STICKING / BEAD OPTIONS

- Standard & custom sticking / bead profiles available
- Options available will vary depending on fire rating

DIMENSIONS^{^*#}

| Door Width | Door Height | Door Thickness | Stile & Top Rail Width | Bottom Rail Width |
|-------------|--------------|---|------------------------|-------------------|
| up to 4'-0" | up to 10'-0" | 1-3/8"(non-rated), 1-3/4", or 2-1/4" | 6"*** | 10" |

[^] Custom sizes and options available, longer lead times may apply. Please refer to the Stile and Rail Component Dimensions Chart for more information

* Component Dimensions are based on nominal opening size of door

Door height & width restrictions vary depending on fire rating restrictions

** Stile width may vary depending on lite opening, hardware, and/or fire rating