

FLAT OR RAISED PANELS

| | |
|--------------------------------------|---|
| DIMENSIONS | DOOR HEIGHT: UP TO 10'-0" WIDTH: UP TO 2'-0" THICKNESS: 1-3/8" (NON-RATED), 1-3/4", OR 2-1/4" STILE & RAIL WIDTH: 2-1/2" STILES ALLOWED ON DOORS UP TO 1'-9" BOTTOM RAIL WIDTH: 10" |
| STILES | PARTICLEBOARD OR DOUBLE REFINED MDF - STILES HAVE HARDWOOD EDGE |
| RAILS | PARTICLEBOARD OR DOUBLE REFINED MDF - SEALED TOP & BOTTOM RAILS |
| GLASS OPTIONS | GLASS OPTIONS VARY ON DOOR SELECTION. CONSULT VT FOR MORE INFORMATION. |
| FINISH | WDMA TR-8/ SYSTEM 10 WATER-BASED UV CURED ACRYLATED POLYURETHANE IS STANDARD. PRIMED AND OPAQUE COATINGS ALSO AVAILABLE. VT COLOR CHOICES ARE AVAILABLE OR CUSTOM COLOR MATCHING BY SUBMITTING A PHYSICAL SAMPLE (MINIMUM 3" X 5") |
| STICKING, PANELS, & MOULDING OPTIONS | <ul style="list-style-type: none"> STANDARD & CUSTOM STICKING / BEAD PROFILES AVAILABLE; OPTIONS AVAILABLE VARY DEPENDING ON FIRE RATING RAISED AND FLAT PANEL OPTIONAL RAISED MOULDING PANELS CAN BE REPLACED WITH GLASS |
| ADHESIVE | TYPE 1 ADHESIVE |
| ACOUSTICAL RATING | REFER TO STC CHART |
| QUALITY STANDARDS | WDMA I.S. 6A & AWS, SECTION 9 QUALITY STANDARDS |
| WDMA PERFORMANCE LEVEL | EXTRA HEAVY DUTY, FIRE COMPOSITE BLOCKING NOT REQUIRED FOR THIS DOOR TYPE |
| SUSTAINABILITY | <ul style="list-style-type: none"> MINIMUM 88% PRE-CONSUMER RECYCLED CONTENT CARB PHASE 2 / TSCA VI COMPLIANT GREENGUARD GOLD FSC UPON REQUEST, CONSULT VT FOR LEED DOCUMENTATION ENVIRONMENTAL PRODUCT DECLARATION (EPD) HEALTH PRODUCT DECLARATION (HPD) |
| DOOR WEIGHT | VARIABLES BY ELEVATION AND SIZE; PLEASE CONSULT WITH VT |
| WARRANTY | LIMITED LIFETIME; INTERIOR USE ONLY. VIEW WARRANTY. |



E605

^ Custom sizes and options available, longer lead times may apply. Please refer to the Stile and Rail Component Dimensions Chart for more information * Component Dimensions are based on nominal opening size of door # Door height & width restrictions vary depending on fire rating restrictions ** Stile width may vary depending on lite opening, hardware, and/or fire rating

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.