



- Doors meet WDMA/AWS Custom or Premium Grade quality standards
- Factory machined to exact requirements for hardware
- FSC® certified upon request (non-rated & 20-minute); NC-COC-000729
- No added urea-formaldehyde (NAUF) available upon request
- Matching wood jambs available
- Split species designs available
- Limited lifetime warranty for interior use

FACTORY FINISH

- WDMA TR-8/ System 10 Water-based UV cured acrylated polyurethane is standard. Primed and opaque coatings also available.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")

Note: Some speices are only available unfinished. Please contact customer service with questions.

STICKING / BEAD OPTIONS

- Standard #104 louver bead, contact sales representative for custom bead availability

Note: Mullion may be required depending on louver size

DIMENSIONS^{^*#}

Door Width	Door Height	Door Thickness	Stile & Top Rail Width	Bottom Rail Width
up to 4'-0"	up to 10'-0"	1-3/8" (non-rated), 1-3/4", or 2-1/4"	6 ^{**}	10"

[^] Custom sizes and options available, longer lead times may apply. Please refer to the Stile and Rail Component Dimensions Chart for more information

* Component Dimensions are based on nominal opening size of door

Door height & width restrictions vary depending on fire rating restrictions

** Stile width may vary depending on lite opening, hardware, and/or fire rating