

EGGERS COLLECTION: STC

MULTI-PLY CONSTRUCTION- SOUND CORE STC 33-40 NON-RATED, 20-, 45-, 60-, & 90-MINUTE POSITIVE PRESSURE

RIM BANDED RAISED PANEL

	DOOR TYPE	DOOR TYPE STILE & RAIL		STYLUS
DIMENSIONS	Opening Type	Single	Pair	Single
	STC Rating	33-40	37	33
	Fire Rating	Non-Rated to 90-Min	Non-Rated	Non-Rated to 20-Min
	Door Thickness	1-3/4" or 2-1/4" (+-1/16")	1-3/4" (+-1/16")	1-3/4" (+-1/16")
	Panel Thickness	1-1/2" - 1-11/16"	1-11/16"	N/A
	Max Size	4'-6" x 8'-0" or 4'-0" x 7'-0"	96" x 97-3/8"	4'-0" x 10'-0"
STILES	Particleboard or double refined MDF - stile have hardwood edge or Fire Composite Material			
RAILS	Particleboard, double refined MDF, or Fire Composite material - sealed top & bottom rails			
PANELS	Particleboard, double refined MDF, or Fire Composite material			
FINISH	WDMA TR-8/ System 10 Water-based UV cured acrylated polyurethane is standard. Primed and opaque coatings also available. VT color choices are available or custom color matching by submitting a physical sample (minimum 3" x 5")			
STICKING, PANELS, & MOULDING OPTIONS	 Standard & custom sticking / bead profiles available; Options available vary depending on fire rating Rim banded raised panel Optional raised moulding 			
ADHESIVE	Type 1 adhesive			
ACOUSTICAL RATING	STC 33-40. Consult VT for lite & glass approvals			
QUALITY STANDARDS	WDMA I.S. 6A & AWS, Section 9 Quality Standards			
WDMA PERFORMANCE LEVEL	Extra heavy duty, fire composite blocking not required for this door type			
SUSTAINABILITY	 Minimum 88% pre-consumer recycled content CARB Phase 2 / TSCA VI Compliant GREENGUARD GOLD FSC upon request, Consult VT for LEED documentation Environmental Product Declaration (EPD) Health Product Declaration (HPD) 			
DOOR WEIGHT	Varies by elevation & size; Please consult with VT			
WARRANTY	Limited lifetime; Interior use only. <u>View warranty</u>			

^ Custom sizes and options available, longer lead times may apply. Please refer to the Stile and Rail Component Dimensions Chart for more information * Component Dimensions are based on nominal opening size of door # Door height & width restrictions vary depending on fire rating restrictions ** Stile width may vary depending on lite opening, hardware, and/or fire rating

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



CUSTOMER

SERVICE

800.827.1615 info@vtindustries.com vtindustries.com

