

HERITAGE COLLECTION: SCLC-3

3-PLY BONDED STRUCTURAL COMPOSITE LUMBER CORE
NON-RATED, 20-, & 45-MINUTE POSITIVE PRESSURE



PRIMED HDF

THICKNESS	1-3/4" (± 1/16")
MAXIMUM SIZE	4'-0" X 10'-0" MAXIMUM, FOR OVERSIZED DOORS PLEASE CONSULT VT; SEE FIRE DOOR CAPABILITY CHART FOR RATED DOORS
CORE	STRUCTURAL COMPOSITE LUMBER CORE, 70% OF DOOR CONSTRUCTION WEIGHT
VERTICAL EDGES (STILES)	STRUCTURAL COMPOSITE LUMBER (SCL) OR FIRE COMPOSITE AS REQUIRED WITH FINISHED MILL OPTION (PRIMED OR PAINTED EDGES)
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	STRUCTURAL COMPOSITE LUMBER (SCL) - SEALED TOP & BOTTOM RAILS
FACES	PRIMED HIGH DENSITY FIBERBOARD (HDF)
STANDARD BEVEL	1/8" IN 2" OR 3°
FINISH	PRIMED; WOOD ACCESSORIES AVAILABLE FINISHED TO MATCH
ADHESIVE	TYPE 1 ADHESIVE
FACTORY MACHINING	PRE-DRILLED HINGE PILOT HOLES; ALL CUTOUTS FOR MORTISE HARDWARE SHOULD BE MADE AT THE FACTORY FROM HARDWARE MANUFACTURER'S TEMPLATES & APPROVED SHOP DRAWINGS
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, SECTION 9 QUALITY STANDARDS (BONDED CORE)
WDMA PERFORMANCE LEVEL	EXTRA HEAVY DUTY
SUSTAINABILITY	<ul style="list-style-type: none">• CARB PHASE 2 / TSCA VI COMPLIANT• GREENGUARD GOLD OR SCS INDOOR ADVANTAGE GOLD• FSC UPON REQUEST, CONSULT VT FOR LEED DOCUMENTATION• ENVIRONMENTAL PRODUCT DECLARATION (EPD)• HEALTH PRODUCT DECLARATION (HPD)
DOOR WEIGHT	APPROX. 6 LBS/SQ. FT.
WARRANTY	LIMITED LIFETIME, INTERIOR USE ONLY. VIEW WARRANTY.



SCLC-3 (5508H, 5P08H, 808H, 8P08H)

ADDITIONAL DOOR FEATURES

CUTOUTS: 5" minimum distance from door edge & the minimum distance between lite & lock cut out is 1-1/2" non-rated & 20-minute, 5" lite to lock (45-minute)

CLEARANCES: 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.

SECURITY RATING: Class 40, ASTM 476 (highest rating possible)

LABELING: Positive pressure, Category A 20-minute Intertek/Warnock Hersey fire labels per NFPA 80 4.2 Fire-rated doors must use approved lite frames. UL 10C

PACKAGING: Doors shall be individually poly-bagged by request for protection & marked as per tag openings on shop drawings

ACCESSORIES: Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others.

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



1000 Industrial Park
Holstein, IA 51025



800.827.1615



info@vtindustries.com
vtindustries.com