

# HERITAGE COLLECTION: SCLC-5

5-PLY BONDED STRUCTURAL COMPOSITE LUMBER CORE  
NON-RATED, 20-, & 45-MINUTE POSITIVE PRESSURE



## WOOD VENEER, HPDL, OR MDO

THICKNESS	1-3/4" (± 1/16")
MAXIMUM SIZE	4'-0" X 10'-0" MAXIMUM, FOR OVERSIZED DOORS PLEASE CONSULT VT; SEE FIRE DOOR CAPABILITY CHART FOR RATED DOORS
CORE	STRUCTURAL COMPOSITE LUMBER CORE, 70% OF DOOR CONSTRUCTION WEIGHT
VERTICAL EDGES (STILES)	STRUCTURAL COMPOSITE LUMBER (SCL) OR FIRE COMPOSITE AS REQUIRED WITH MATCHING/COMPATIBLE WOOD/VENEER, MATCHING HPDL OR FINISHED MILL OPTION (PRIMED OR PAINTED) EDGES
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	STRUCTURAL COMPOSITE LUMBER (SCL) - SEALED TOP & BOTTOM RAILS
FACES	WOOD VENEER, HPDL HORIZONTAL GRADE STANDARD (HGS) MEETS NEMA STANDARD LD-3, OR MDO
CROSSBANDS	HIGH DENSITY FIBERBOARD (HDF), 20% OF DOOR CONSTRUCTION WEIGHT, PRE-CONSUMER RECYCLED MATERIAL
STANDARD BEVEL	1/8" IN 2" OR 3°
FINISH	PRIMED OR OPAQUE FACTORY PAINT
VENEER MATCH / FACE ASSEMBLY	BOOK MATCH STANDARD. SLIP OR RANDOM AVAILABLE; FACE ASSEMBLY: RUNNING MATCH STANDARD, CENTER, BALANCED, OR CENTER BALANCED AVAILABLE
ADHESIVE	TYPE 1 ADHESIVE
FACTORY MACHINING	PRE-DRILLED HINGE PILOT HOLES; ALL CUTOUTS FOR MORTISE HARDWARE SHOULD BE MADE AT THE FACTORY FROM HARDWARE MANUFACTURER'S TEMPLATES & APPROVED SHOP DRAWINGS
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, SECTION 9 QUALITY STANDARDS (BONDED CORE)
WDMA PERFORMANCE LEVEL	EXTRA HEAVY DUTY
SUSTAINABILITY	<ul style="list-style-type: none"><li>• CARB PHASE 2 / TSCA VI COMPLIANT</li><li>• GREENGUARD GOLD OR SCS INDOOR ADVANTAGE GOLD</li><li>• FSC UPON REQUEST, CONSULT VT FOR LEED DOCUMENTATION</li><li>• ENVIRONMENTAL PRODUCT DECLARATION (EPD)</li><li>• HEALTH PRODUCT DECLARATION (HPD)</li></ul>
DOOR WEIGHT	APPROX. 6 LBS/SQ. FT.
WARRANTY	LIMITED LIFETIME, INTERIOR USE ONLY. <a href="#">VIEW WARRANTY.</a>



SCLC-5 (5508H, 5P08H, 808H, 8P08H)

### ADDITIONAL DOOR FEATURES

**PAIRS & SETS:** Pair match standard, set match available

**DOORS/TRANSOMS:** Continuous match standard, End or no match available

**CUTOUTS:** 5" minimum distance from door edge & the minimum distance between lite & lock cut out is 1-1/2" non-rated & 20-minute, 5" lite to lock (45-minute)

**CLEARANCES:** 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.

**SECURITY RATING:** Class 40, ASTM 476 (highest rating possible)

**LABELING:** Positive pressure, Category A 20-minute Intertek/Warnock Hersey fire labels per NFPA 80 4.2 Fire-rated doors must use approved lite frames. UL 10C

**PACKAGING:** Doors shall be individually poly-bagged by request for protection & marked as per tag openings on shop drawings

**ACCESSORIES:** Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others.

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



1000 Industrial Park  
Holstein, IA 51025



800.827.1615



info@vtindustries.com  
vtindustries.com