



Architectural
Wood Doors

PALLADIUM COLLECTION

BULLET RESISTANT DOORS
NON-RATED, BULLET RESISTANCE LEVELS 1-8

INPRO RIGID VINYL – FIXED VINYL EDGE

THICKNESS	1-3/4", 2-1/4" (± 1/16")
SIZE	Size limitations by weight, consult VT; Refer to Bullet Resistance Technical Bulletin for door weights
CORE	Bullet Resistant Core (UL 752 1-8; N.I.J. 0108.01 IIA-III)
VERTICAL EDGES (STILES)	Structural Composite Lumber (SCL) with matching fixed vinyl edge
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) - Sealed Top & Bottom Rails
FACES	Inpro® Rigid Vinyl (.040")
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, Pre-consumer recycled material
STANDARDS	Bevel: 1/8" in 2" or 3° Type 1 Polyvinyl Acetate (PVA) Adhesive
FINISH	Woodgrains, Solid Colors, and Elements
HARDWARE/LITES	Butt Hinges, Electric Hinges, Cylindrical Locks, Mortise Locks, Rim and Surface Exit Devices, limitations may apply Refer to Bullet Resistant Technical Bulletin for hardware limitations Pre-drilled hinge pilot holes Refer to Lite/Lock Cutout Margins Technical Bulletin
ACOUSTICAL RATING	N/A
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core) Premium Grade
WDMA PERFORMANCE LEVEL	Extra Heavy Duty
SUSTAINABILITY	CARB Phase 2 / TSCA VI Compliant FSC® upon request, consult VT for LEED documentation Environmental Product Declaration (EDP) Refer to VT Sustainability page
WARRANTY	Limited Lifetime, Interior use only, reference VT Warranty

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



CUSTOMER
SERVICE

800.827.1615
info@vtindustries.com
vtindustries.com



© 2026 VT Industries, Inc. All rights reserved 09-2026