



**Architectural
Wood Doors**

PALLADIUM COLLECTION

FOAM CORE DOORS
NON-RATED
NEENAH/TWO RIVERS ONLY

INPRO RIGID VINYL – FIXED EDGE

THICKNESS	1-3/8", 1-3/4" or 2-1/4" (± 1/16")
SIZE	3'-0" x 7'-0" at 1-3/8" thickness; 4'-0" x 10'-0" at 1-3/4" or 2-1/4" thickness
CORE	Modified EPS Foam Core
VERTICAL EDGES (STILES)	Structural Composite Lumber (SCL) with matching fixed vinyl edge
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) - Sealed Top & Bottom Rails
FACES	Inpro® Rigid Vinyl (.040")
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, Pre-consumer recycled material
STANDARDS	Bevel: 1/8" in 2" or 3° Type 1 Polyvinyl Acetate (PVA) Adhesive
FINISH	Woodgrains, Solid Colors, and Elements
HARDWARE/LITES	Butt Hinges, Electric Hinges, Cylindrical Locks, Mortise Locks, Rim and Surface Exit Devices, limitations may apply Pre-drilled hinge pilot holes Refer to Lite/Lock Cutout Margins Technical Bulletin
ACOUSTICAL RATING	N/A
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core) Premium Grade
WDMA PERFORMANCE LEVEL	N/A
SUSTAINABILITY	CARB Phase 2 / TSCA VI Compliant FSC® upon request, Environmental Product Declaration (EPD), Health Product Declaration (HPD) Refer to VT Sustainability page
WARRANTY	One year from date of original installation-not available for exterior installations, reference VT Warranty

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



**CUSTOMER
SERVICE**

800.827.1615
info@vtindustries.com
vtindustries.com



© 2026 VT Industries, Inc. All rights reserved 09-2026