



Architectural
Wood Doors

PALLADIUM COLLECTION

WICKET DOORS
NON-RATED, STRUCTURAL COMPOSITE LUMBER

INPRO RIGID VINYL – REMOVABLE EDGE

THICKNESS	1-3/4" (± 1/16")
SIZE	Refer to Wicket Doors Technical Bulletin
CORE	Structural Composite Lumber Core (SCLC), 70% of door construction weight
VERTICAL EDGES (STILES)	Hardwood with matching removable vinyl or stainless steel edge Access Door: Lumber only
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) - Sealed Top & Bottom Rails Access Door: Lumber only
FACES	Inpro® Rigid Vinyl (.040")
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, Pre-consumer recycled material
STANDARDS	Bevel: 1/8" in 2" or 3° Type 1 Polyvinyl Acetate (PVA) Adhesive
FINISH	Woodgrains, Solid Colors, and Elements
HARDWARE/LITES	Refer to Wicket Doors Technical Bulletin for capabilities and exclusions
ACOUSTICAL RATING	N/A
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core) Premium Grade
WDMA PERFORMANCE LEVEL	Extra Heavy Duty
SUSTAINABILITY	CARB Phase 2 / TSCA VI Compliant GREENGUARD GOLD FSC® upon request, consult VT for LEED documentation Environmental Product Declaration (EDP) Health Product Declaration (HPD) Refer to VT Sustainability page
WARRANTY	Limited Lifetime, Interior use only, reference VT Warranty

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



CUSTOMER
SERVICE

800.827.1615
info@vtindustries.com
vtindustries.com



© 2026 VT Industries, Inc. All rights reserved 09-2026