

Prefit and Premachined Door Schedule



Frame Manufacturer <input type="text"/> or <input type="checkbox"/> Existing Frame Opening Size <input type="text"/> X <input type="text"/> Frame Type <input type="checkbox"/> Steel <input type="checkbox"/> Wood <input type="checkbox"/> Aluminum Thickness <input type="text"/> Prefit Door Size <input type="text"/> X <input type="text"/> X <input type="text"/>	Face Species and Cut <input type="text"/> Face Grade A AA Core Type <input type="text"/> Face Matching <input type="text"/> Palladium Edge Door Application Interior Exterior <input type="checkbox"/> Fixed <input type="checkbox"/> Removable	Finish Approval #: <input type="text"/> Primed Painted Unfinished Plam or HPDL edge Finish HPDL (STD) Finished Painted Unfinished	Page <input type="text"/> Flush Stile & Rail
---	--	---	---

Label Doors Rated NR 20 45 60 90 Enviromental: FSC FSC Controlled NAUF None	Louver Size W <input type="text"/> X L <input type="text"/> Lockstile <input type="text"/> <input type="checkbox"/> Centered BTM Rail <input type="text"/> Type <input type="text"/> <input type="checkbox"/> Cutout Only	Lite <input type="checkbox"/> Cutout Size <input type="checkbox"/> Visible Lite Special Detail # <input type="text"/> Wood Stop <input type="text"/> or MVP# <input type="text"/> or Cutout Only <input type="checkbox"/> Glass Thickness <input type="text"/> Type <input type="text"/> Size W <input type="text"/> x L <input type="text"/> Top Rail <input type="checkbox"/> Lockstile <input type="text"/> <input type="checkbox"/> Centered Size W <input type="text"/> x L <input type="text"/> Top Rail <input type="checkbox"/> Lockstile <input type="text"/> <input type="checkbox"/> Centered Glass By <input type="checkbox"/> VT <input type="checkbox"/> Others Pattern to Face <input type="checkbox"/> Inside <input type="checkbox"/> Outside
--	---	--

Active Lock Hinge Inactive Lock Hinge	STC Rating
Bevel Square Radius	Seal System

Hinges / Pivots

Size Mfg. No.
 Gauge Template No.

Top of Door to Top of Hinge

Hinge Backset

Lock & Exit

Manufacturer
 Model
 Template
 Trim Template
 Backset

Top of Door to C/L of Lock

Lock Strike

2- 3/4 ASA
 4- 7/8 ASA
 Special

Deadlock Strike 2-3/4 3-1/2
 Lip No Lip

Mortise Holder/Stop

Mfr
 Model
 Template
 Degree
 Dead Stop Yes No

Flush Bolts-Temp. Rod Length

Mfr Top Top only
 Model Bottom

Flush Door Top (5) Bottom (5)
 Blocking
 Lock block(s):

Other Hardware Remarks/Raceway

Stile & Rail Door Options (Please provide an elevation for all stile & rail doors) Stile & Rail Elevation Code

Panels Membrane Raised Flat Rim-Banded Raised

Profile Quarter Round Ovolo Ogee Square

Stile Width (std. 6") Top Rail (std. 6") Bottom Rail (std. 10") Lock Rail (std. 6")

Total Doors on this Page:

Door No.	Swing