

WOOD JAMBS

VT ARCHITECTURAL WOOD DOORS



NON-RATED JAMBS AND SIDELITES

	Jamb and Sidelite
Jamb Size	Standard non-rated jamb is $\frac{3}{4}$ " flat jamb with 1-1/2" x 5/8" lumber T-stop Minimum 3/4" thick MDF filler, 3-3/4" minimum width
Overall Opening	14'-2" x 11'-6" maximum
Single Door Opening	4'-0" x 9'-0" maximum
Pair Door Opening	8'-0" x 9'-0" maximum
Wood Density	Minimum 30#/cu. ft. Paint Grade Poplar OK
T-stop	Minimum 1/2" x 1-1/2" (5/8" overall thickness)
Shim Space	Maximum 1/2"—if greater than 1/4" must be filled with fiberglass
Casing	Minimum 3/8" x 1-3/4"—casing may be supplied by others (custom profiles available)
Lite Stops	Minimum 3/4" x 1-1/8"
Panels	Maximum 48" x 116" installed with minimum 3/4" x 1-1/8" panel stop 2-sides
Lite Opening/Transom	Maximum 36" x 96" or 96" x 36"
Glass	Fire and safety rated glass required—VT does not supply glass
Hardware	Hinges: steel mortise butt hinges or continuous hinge per NFPA 80. Strikes: steel mortise or surface applied for listed flushbolts, deadlocks, latchsets, or exit devices. Track for listed closer with maximum mortise 1-1/4" wide x 13/16" deep x 17-5/16" long with minimum 3/4" stop at head and HSS2000 applied to stop. Silencer buttons surface applied only.
Options	Jamb may be veneered MDF or solid lumber
Corner Detail	Square cut only—header runs through

1000 INDUSTRIAL PARK • HOLSTEIN, IA 51025 • 800.827.1615
ONE EGGERS DRIVE • TWO RIVERS, WI 54241 • 920.793.1351