



# Product Update

JULY 25, 2019

#P465

Revision 01

## DOORS WITH TOP & BOTTOM PIVOT ONLY

VT's warranty now covers non-rated doors, 1-3/4" through 2-1/4" thick hung on top and bottom pivots only. This coverage includes Stile & Rail doors as well as flush doors constructed using Particleboard, SCL, Stave Lumber or Agrifiber core. It also includes lead doors constructed with these core types. In addition to regular offset pivot applications, this coverage will now allow center hung doors to carry our full warranty.

This coverage includes applications where a top pivot is used in combination with a floor closer (where the floor closer includes a pivot arm). It is the responsibility of the door specifier to insure the selected hardware is appropriate for the door weight and application, and that both pivots have the same offset. This warranty coverage does not apply for doors that also include molding or appliques to one face only or have different species or finish on the faces.

This warranty coverage applies to:

Door Type	Maximum Width	Maximum Height
Flush Particle, Agrifiber, and Stave Core	4'	8'
Flush Structural Composite Core	4'	9'
Stile & Rail Doors	4'	8'

### Notes:

- This coverage only applies to non-labeled doors. NFPA-80 requires labeled fire doors to have 2 hinges (or pivots) on doors up to 5' tall and an additional hinge (or pivot) for each 30" or fraction thereof.
- Special warranty coverage involving different maximum heights or alternate core types than noted above may apply to OEM accounts or on a job-specific basis.