



HERITAGE & PALLADIUM COLLECTION

SPECIFICATION CHECKLIST

INDUSTRY STANDARD

- ☐ AWS EDITION 2
- ☐ WDMA I.S 1A INDUSTRY STANDARD FOR ARCHITECTURAL WOOD FLUSH DOORS

DOOR CONSTRUCTION

AESTHETIC GRADE

- ☐ PREMIUM
- ☐ CUSTOM

WOOD FACE REQUIREMENTS

VENEER GRADE

- ☐ A
- ☐ AA

CHOOSE A FACE VENEER

- ☐ SPECIES
- ☐ CUT
- ☐ PLAIN SLICED/ FLAT CUT
 - ☐ QUARTER CUT
 - ☐ RIFT CUT (OAK ONLY)
 - ☐ ROTARY CUT (NOT AVAILABLE IN SOME SPECIES)

VENEER PIECE MATCH**

- ☐ BOOK (INDUSTRY STANDARD)
- ☐ SLIP
- ☐ RANDOM

VENEER FACE MATCH

- ☐ RUNNING (INDUSTRY STANDARD)
- ☐ BALANCE
- ☐ CENTER

APPEARANCE OF PAIRS, SETS, & TRANSOMS

- ☐ MATCHED
- ☐ NOT MATCHED

PERFORMANCE DUTY LEVEL

- ☐ EXTRA HEAVY DUTY
- ☐ HEAVY DUTY

CORE TYPE

- ☐ PARTICLEBOARD (PC)
- ☐ STRUCTURAL COMPOSITE LUMBER (SCLC)
- ☐ FIRE RESISTANT COMPOSITE (FD)
- ☐ AGRIFIBER

HARDWARE REINFORCEMENT BLOCKING

- ☐ PC DOORS
- ☐ FD DOORS
- ☐ AGRIFIBER DOORS

CORE/EDGE INTERFACE

- ☐ BONDED

VINYL EDGE REQUIREMENT

- ☐ REMOVABLE
- ☐ FIXED

FIRE DOOR TEST METHOD

- ☐ NEGATIVE PRESSURE: UL 10B, IBC
- ☐ POSITIVE PRESSURE: UL 10C, IBC
- ☐ CATEGORY A
 - ☐ CATEGORY B

FIRE DOOR CONSTRUCTION

- ☐ NO METAL MEETING EDGES
- ☐ METAL EDGES
- ☐ CONCEALED VERTICAL RODS

HPDL FACE REQUIREMENTS

- ☐ MANUFACTURER
- ☐ THICKNESS
- ☐ PATTERN/COLOR/FINISH

MACHINING REQUIREMENTS

- ☐ FACTORY MACHINED FOR HARDWARE
- ☐ FACTORY DRILLED PILOT HOLES FOR HINGES

FINISH REQUIREMENTS

FINISH SYSTEM

- ☐ UV-CURED FACTORY FINISHING BY MANUFACTURER
- ☐ OP-4 (WDMA) / OP-5 (AWS)
- ☐ OTHER FINISH APPLICATIONS

LEED REQUIREMENTS

- ☐ RECYCLED CONTENT
- ☐ RAPIDLY RENEWABLE MATERIALS
- ☐ CERTIFIED WOOD
- ☐ LOW-EMITTING

SPECIFY LITE DOOR OPTIONS

- ☐ INSTALLATION
- ☐ WOOD BEADS
 - ☐ METAL VISION PANELS
 - ☐ VENEER METAL VISION PANELS
- ☐ SPECIAL PERFORMANCE
- ☐ FIRE RATING
 - ☐ X-RAY SHIELDING
 - ☐ ACOUSTICAL
 - ☐ BULLET-RESISTANT
- SPECIAL GLAZING
- ☐ THICKNESS
 - ☐ PATTERN / TEXTURE
 - ☐ SHAPE
 - ☐ PERFORMANCE
 - ☐ OPAQUE

SPECIAL FUNCTION DOORS

- ☐ SOUND RESISTANT (STC)
- ☐ LEAD LINED (X-RAY)
- ☐ BULLET-RESISTANT
- ☐ IMPACT RESISTANT

VINYL FACE REQUIREMENTS

- ☐ INPRO RIGID VINYL
- ☐ PATTERN/COLOR

* Based on chosen industry standard.** Slip is recommended for Rift Oak and all other quartered species.

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.



EGGERS STILE & RAIL COLLECTION

SPECIFICATION CHECKLIST

INDUSTRY STANDARD

- ☐ AWS EDITION 2
- ☐ WDMA 1.S 6A-11: INDUSTRY STANDARD FOR ARCHITECTURAL STILE & RAIL DOORS

DOOR CONSTRUCTION

AESTHETIC GRADE

- ☐ PREMIUM
- ☐ CUSTOM

WOOD FACE REQUIREMENTS

VENEER GRADE

- ☐ A
- ☐ AA

CHOOSE A FACE VENEER

- ☐ SPECIES
- ☐ CUT
- ☐ PLAIN SLICED/ FLAT CUT
- ☐ QUARTER CUT
- ☐ RIFT CUT (OAK ONLY)
- ☐ ROTARY CUT (NOT AVAILABLE IN SOME SPECIES)

VENEER PIECE MATCH**

- ☐ BOOK (INDUSTRY STANDARD)
- ☐ SLIP
- ☐ RANDOM

VENEER FACE MATCH

- ☐ RUNNING (INDUSTRY STANDARD)
- ☐ BALANCE
- ☐ CENTER

APPEARANCE OF PAIRS, SETS, & TRANSOMS

- ☐ MATCHED
- ☐ NOT MATCHED

DOOR TYPE

- ☐ PANEL
- ☐ GLASS
- ☐ LOUVER
- ☐ COMBINATION

PANEL TYPE

- ☐ RAISED
- ☐ MEMBRANE PRESSED
- ☐ RIM BANDED
- ☐ SPECIAL
- ☐ FLAT
- ☐ NONE

STICKING TYPE

- ☐ QUARTER ROUND
- ☐ OVOLO
- ☐ OGEE
- ☐ SQUARE
- ☐ SPECIAL
- ☐ NONE

FIRE DOOR TEST METHOD

- ☐ NEGATIVE PRESSURE: UL 10B, IBC
- ☐ POSITIVE PRESSURE: UL 10C, IBC
- ☐ CATEGORY A
- ☐ CATEGORY B

FIRE DOOR CONSTRUCTION

- ☐ NO METAL MEETING EDGES
- ☐ METAL EDGES
- ☐ CONCEALED VERTICAL RODS

SPECIAL FUNCTION DOORS

- ☐ SOUND RESISTANT (STC)
- ☐ LEAD LINED (X-RAY)
- ☐ BULLET-RESISTANT
- ☐ IMPACT RESISTANT

MACHINING REQUIREMENTS

- ☐ FACTORY MACHINED FOR HARDWARE
- ☐ FACTORY DRILLED PILOT HOLES FOR HINGES

FINISH REQUIREMENTS

FINISH SYSTEM

- ☐ UV-CURED FACTORY FINISHING BY MANUFACTURER
- ☐ OP-4 (WDMA) / OP-5 (AWS)
- ☐ OTHER FINISH APPLICATIONS

LEED REQUIREMENTS

- ☐ RECYCLED CONTENT
- ☐ RAPIDLY RENEWABLE MATERIALS
- ☐ CERTIFIED WOOD
- ☐ LOW-EMITTING

SPECIFY LITE DOOR OPTIONS

- ☐ INSTALLATION
- ☐ WOOD BEADS
- ☐ METAL VISION PANELS
- ☐ VENEER METAL VISION PANELS
- ☐ SPECIAL PERFORMANCE
- ☐ FIRE RATING
- ☐ X-RAY SHIELDING
- ☐ ACOUSTICAL
- ☐ BULLET-RESISTANT
- SPECIAL GLAZING**
- ☐ THICKNESS
- ☐ PATTERN / TEXTURE
- ☐ SHAPE
- ☐ PERFORMANCE
- ☐ OPAQUE

* Based on chosen industry standard.** Slip is recommended for Rift Oak and all other quartered species.

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.

