

COMMERCIAL PAINTABLE SURFACE

THICKNESS	1-3/4" (± 1/16")
MAXIMUM SIZE	4'-0" X 8'-0" MAXIMUM
CORE	SOLID PARTICLEBOARD CORE, MAT FORMED WOOD PARTICLEBOARD MEETS / EXCEEDS ALL INDUSTRY REQUIREMENTS INCLUDING ANSI A 208.1, LD-1 OR LD-2
STILES	1-1/16" WOOD, MATCHING OR COMPATIBLE TO FACES; BEFORE TRIM
RAILS	1" TOP RAIL, 2-1/2" BOTTOM RAIL; BEFORE TRIM
FACES	CROSS-BANDED HARDWOOD VENEER. 1/8" PRIMED HARDBOARD. 1/8" PREFINISHED SMOOTH OR GRAINED HARDBOARD.
CONSTRUCTION	5-PLY WHEN USING 2-PLY HARDWOOD FACES
VERTICAL EDGES	(VISIBLE SURFACE) FINISHED MILL OPTION
ADHESIVE	ANSI/WDMA I.S. 1-A-04 TYPE 1 OR 2 PVA GLUE
FACTORY MACHINING	MACHINING FOR HARDWARE. HARDWARE CUTOUTS SHALL BE FACTORY MACHINED FROM MANUFACTURER'S & APPROVED SHOP DRAWINGS
SUSTAINABILITY	<ul style="list-style-type: none"> <li>• CARB PHASE 2 / TSCA VI COMPLIANT</li> <li>• GREENGUARD GOLD OR SCS INDOOR ADVANTAGE GOLD</li> <li>• ENVIRONMENTAL PRODUCT DECLARATION (EPD)</li> </ul>
DOOR WEIGHT	28 LBS / CU. FT.
WARRANTY	5-YEAR LIMITED WARRANTY FOR INTERIOR USE ONLY.



COMMERCIAL PAINTABLE SURFACE

ADDITIONAL DOOR FEATURES & STANDARDS

CUTOUTS: 5" minimum distance from door edge & the minimum distance between lite & lock cut out is 3-5/16

CLEARANCES: 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7.1. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.1

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.