


Schedule B Wood Door Specification Sheet

Specification Sheet

WDMA Wood Door Identification		Core Types Use WDMA symbols at left	
WDMA Spec Symbol	Door Construction Core		
PC-3	3 Ply particleboard core		
PC-5	5 Ply particleboard core	Face Veneers Specify grade, cut and species required _____	
SLC-5	5 Ply stave lumber core	Stiles (Side Edges) <input type="checkbox"/> Painted/Stained <input type="checkbox"/> Same	
SCLC-5	5 Ply structural lumber core	Top/Bottom Rails SCL U.N.O.	
FD-5	1 1/2 Hour labeled fire door (90 min) (B)		
FD-5	1 Hour labeled fire door (60 min) (B)		
FD-5	3/4 Hour labeled fire door (45 min) (C)	Glass Openings Specify moulding type and glass thickness _____	
STC	Sound Retardant (STC Rated)	Louvers Specify louver type _____	
LL-7	Lead lined		
WSPC-5	5 Ply Agrifiber core	Prefit clearances Standard for hinged doors 1/8" top, 5/8" bottom, singled 1/4" width, pairs 3/16" width, Specify double egress width and if other clearances are required	
<p>Note:</p> <p>a. Types PC-3, PC-5, SCLC-5, SLC-5 and STC, LL-7 and WSPC-5 are available with 20 minute label</p> <p>b. When labeled doors are required fill in the Fire Label column on the Door Schedule</p> <p>c. All fire doors subject to size and other label restrictions</p> <p>VT Industries does not prep any thru-bolt holes less than 1/4" in diameter. VT Industries does prep pilot holes for butt hinges.</p> <p>Packaging: Individual polybag as standard</p>		Edge Machining Standard for hinged doors bevel both hinge and lock edge 1/8" in 2". Specify other edge machining requirements:	
		Finishing <input type="checkbox"/> At Factory <input type="checkbox"/> By Others (Field) If factory finished, Approved color sample no.	
		Remarks	
		Job Name	
 Specification Sheet		Date	Revisions By
		Drawn By	Date
		Contract/Job	Schedule B Sheet
			_____ of _____



1000 Industrial Park • P.O. Box 490 • Holstein, IA 51025
 712.369.4381 • 800.827.1615 • FAX 712.369.4111
 www.vtindustries.com • sales@vtindustries.com